

HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0

Print Date 07/16/2014

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : HORIZON TACOMA GRAY MATTE 5-GAL
 Product code : TBS520-600 805

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION
Emergency Overview

Gray. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Prolonged or repeated exposure to vapors of isopropyl alcohol can cause eye, skin, or respiratory irritation, headache, dizziness, nausea, in coordination, drowsiness, and loss of consciousness. Prolonged or repeat exposure to liquid can cause defatting, drying, and irritation of the skin dermatitis. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	15.0 - 40.0
Acrylic polymer(s)	NJ TSRN# 51721300-5434P	15.0 - 40.0
Calcium carbonate	471-34-1	15.0 - 40.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Propylene glycol	57-55-6	3.0 - 7.0
Inert Filler	NJ TSRN# 51721300-5013P	1.0 - 5.0
2-Propanol	67-63-0	1.0 - 5.0



HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0

Print Date 07/16/2014

REVISION DATE: 07/08/2012

Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0
Formaldehyde	50-00-0	- <0.1
Trichloromethane	67-66-3	- <0.1

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.
- Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not applicable.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0

Print Date 07/16/2014

REVISION DATE: 07/08/2012

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Inert Filler	NJ TSRN# 51721300-5013P	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction.
2-Propanol	67-63-0	OSHA PEL: ACGIH TWA: ACGIH STEL:	980 mg/m3 200 ppm 400 ppm	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Trichloromethane	67-66-3	ACGIH TWA:	10 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Gray
- Odor : Ammonia
- pH : 9 - 10

HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0

Print Date 07/16/2014

REVISION DATE: 07/08/2012

Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: < 0 °C, < 32 °F
Freezing point	: Not available.
Boiling point/range	: 212 °F, 100 °C
Water solubility	: Soluble
Specific Gravity	: 1.03
% Volatile Weight	: 34 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.
Stability	: Stable
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Calcium carbonate, CAS-No.: 471-34-1 Acute oral toxicity (LD-50 oral)	6,450 mg/kg (Rat)
Propylene glycol, CAS-No.: 57-55-6 Acute oral toxicity (LD-50 oral)	30,000 mg/kg (Rat) 18,000 mg/kg (Rabbit) 19,000 mg/kg (Dog) 23,900 - 31,800 mg/kg (Mouse) 18,400 - 196,000 mg/kg (Guinea pig)
2-Propanol, CAS-No.: 67-63-0 Acute oral toxicity (LD-50 oral)	4,700 - 5,800 mg/kg (Rat) 6,410 mg/kg (Rabbit) 4,797 mg/kg (Dog) 3,600 mg/kg (Mouse) 8,000 mg/kg (Rabbit) 5,045 mg/kg (Rat) 4,797 mg/kg (Dog) 3,600 mg/kg (Mouse) 6,410 mg/kg (Rabbit) 8,000 mg/kg (Rabbit) 4,700 - 5,800 mg/kg (Rat) 5,045 mg/kg (Rat)
Acute dermal toxicity (LD-50 dermal)	5,030 - 7,900 mg/kg (Rabbit) 12,800 mg/kg (Rabbit) 5,030 - 7,900 mg/kg (Rabbit) 12,800 mg/kg (Rabbit)
Formaldehyde, CAS-No.: 50-00-0 Acute oral toxicity (LD-50 oral)	800 mg/kg (Rat) 260 mg/kg (Guinea pig) 100 mg/kg (Rat) 42 mg/kg (Mouse)
Acute inhalation toxicity (LC-50)	0.82 mg/l for 30 min (Rat) 0.48 mg/l for 4 h (Rat) 0.414 mg/l for 4 h (Mouse) 0.4 mg/l for 2 h (Mouse)
Trichloromethane, CAS-No.: 67-66-3 Acute oral toxicity (LD-50 oral)	1,117 mg/kg (Rat) 36 mg/kg (Mouse) 908 mg/kg (Rat) 2,250 mg/kg (Dog) 9,827 mg/kg (Rabbit) 2,180 mg/kg (Rat) 2,250 mg/kg (Dog) 36 mg/kg (Mouse) 9,827 mg/kg (Rabbit) 1,117 mg/kg (Rat) 2,180 mg/kg (Rat) 908 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	47.702 mg/l (Rat) 47.702 mg/l for 4 h (Rat)



HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0
REVISION DATE: 07/08/2012

Print Date 07/16/2014

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Titanium dioxide	13463-67-7
Inert Filler	NJ TSRN# 51721300-5013P
2-Propanol	67-63-0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Trichloromethane	67-66-3

OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:



HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0

Print Date 07/16/2014

REVISION DATE: 07/08/2012

OSHA Flammability : Not Regulated

Regulatory VOC (less water and exempt solvent) : 65 g/l

VOC Method 310 : 4 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components : Calcium carbonate 471-34-1
Titanium dioxide 13463-67-7
Inert Filler NJ TSRN# 51721300-5013P
2-Propanol 67-63-0
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
Formaldehyde 50-00-0
Trichloromethane 67-66-3

Penn RTK Components : Water 7732-18-5
Acrylic polymer(s) NJ TSRN# 51721300-5434P
Calcium carbonate 471-34-1
Titanium dioxide 13463-67-7
Propylene glycol 57-55-6
Inert Filler NJ TSRN# 51721300-5013P
2-Propanol 67-63-0

NJ RTK Components : Water 7732-18-5
Acrylic polymer(s) NJ TSRN# 51721300-5434P
Calcium carbonate 471-34-1
Titanium dioxide 13463-67-7
Propylene glycol 57-55-6
2-Propanol 67-63-0
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Components under California Proposition 65:
WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



HORIZON TACOMA GRAY MATTE 5-GAL

Version 2.0
REVISION DATE: 07/08/2012

Print Date 07/16/2014

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System